

X91+

Survey & Engineering

- 220 channels multi-constellation receiver
- Compact and rugged design for demanding field
- Outstanding RTK initialization and centimeter level position accuracy
- Built-in network and UHF modem
- Optional TRx UHF



X91+ GNSS is a compact GNSS receiver designed for high accuracy and productivity even in harsh environments.

With the easy-to-use, efficient and intuitive workflow, compact and rugged structure, X91+ is designed for advanced network RTK survey and the perfect choice for demanding survey applications.

X91+ is fully integrated with GNSS engine, antenna, Bluetooth communication, UHF and network modem in one single unit makes your daily work simple.

By combining decades of positioning and surveying, X91+ GNSS is one of the most powerful GNSS RTK solutions, with no compromise to quality but at an affordable price for every surveyor.



■ Technical Specifications

GNSS Characteristics

- 220 channels with all in view simultaneously tracked satellite signals
 - GPS: L1C/A, L2C, L2E, L5
 - GLONASS: L1C/A, L1P, L2C/A, L2P, L3
 - SBAS: WAAS, EGNOS, MSAS
 - Galileo: E1, E5A, E5B
 - BDS: B1, B2
- Advanced multipath mitigation technology
- Low noise carrier phase measurement

GNSS Accuracies ⁽¹⁾

- Real Time Kinematics (RTK):
 - Horizontal: 8 mm + 1 ppm RMS
 - Vertical: 15 mm + 1 ppm RMS
 - Initialization Time: Typically < 10 s
 - Initialization Reliability: Typically > 99.9%
- Post-processing Static:
 - Horizontal: 3 mm + 0.1 ppm RMS
 - Vertical: 5 mm + 0.4 ppm RMS
 - Baseline Length: ≤ 300 km

Communications

- Serial: 1 x 10-pin LEMO port (external power, USB data download, USB update, RS-232)
- Integrated 3G network modem
- Bluetooth®: V2.0
- CHC UHF Modem Internal Rx: 450 MHz to 470 MHz
- Optional UHF modem⁽²⁾:
 - Internal Rx/Tx: 403 MHz to 473 MHz, up to 1 W
 - External Tx DL6: 5 W to 28 W adjustable
- Protocols:
 - RTCM2.x, RTCM3.x, CMR, CMR+, SCMRX input and output
 - NMEA 0183 output
 - HCN outputs for GNSS raw data (convertible to RINEX static format)
- Data Storage:
 - 4 GB internal memory
 - GPS device mounts as a USB external hard drive

Physical

- Size (H x D): 85 mm x 180 mm (3.3 in x 7.1 in)
- Weight: 1.35 kg (47.6 oz) with battery
- Environment:
 - Operating: -40°C to +65°C (-40°F to +149°F)
 - Storage: -40°C to +75°C (-40°F to +167°F)
- Humidity: 100% condensation
- Dust and Water Proof: IP67
- Shock and Vibration: 2 m (6.6 ft) fall onto concrete

Electrical

- Power Consumption: 2.6 W (depending on user settings)
- Li-ion Battery Capacity: 3400 mAh
- Operating Time⁽³⁾: Up to 6 h in RTK mode
- External Power: 9 V DC to 18 V DC

Software (optional)

- CHC LandStar 7 Android field data collection software
- MicroSurvey Field Genius field data collection software
- Carlson SurvCE field data collection software

(1) Accuracy and reliability specifications may be affected by multipath, satellite geometry and atmospheric conditions. Performances assume the minimum of 5 satellites, follow up of recommended general GPS practices. (2) UHF type approvals are country specific. (3) Operating time varies based on temperature.

Specifications are subject to change without notice.

© 2018 Shanghai Huace Navigation Technology Ltd. All rights reserved. The Bluetooth® world mark and logos are owned by Bluetooth SIG, Inc. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners – Rev. Mar 2018

CHC - Shanghai Huace Navigation Technology Ltd.
599 Gaojing Road, Building D
Shanghai, 201702, China
Tel : +86 21 542 60 273