

# M5

## Survey & Engineering

- 384 channels multi-constellation receiver
- Multiple frequency for GPS, GLONASS and BDS
- Integrated network, UHF modem and Bluetooth
- Compact and rugged design
- Cost-effective GNSS RTK



M5 GNSS receiver is one of the most cost-effective solution selected by large number of surveyors for its outstanding performances and reliability.

Outstanding 384 channels multi-constellation tracking supports GPS, GLONASS and BDS for obstructed sky conditions to guarantee RTK accuracy and reliability in field.

Perfect compatibility with Android based field surveying software LandStar 7 provides a epoch-making experience for various and flexible working industries.

M5 innovative design integrates a built-in GNSS core, multi-constellation antenna, Bluetooth communication, RX UHF data link and network modules in one single receiver.

M5 GNSS receiver brings extremely affordable GNSS RTK solution to surveyors without high cost.



# ■ Technical Specifications

## GNSS Characteristics

- 384 channels with all in view simultaneously tracked satellite signals
  - GPS: L1, L2, L5
  - GLONASS: L1, L2
  - BDS: B1, B2, B3
- Advanced multipath mitigation technology
- Low noise carrier phase measurement

## GNSS Accuracies <sup>(1)</sup>

- Real Time Kinematics (RTK):
  - Horizontal: 10 mm + 1 ppm RMS
  - Vertical: 15 mm + 1 ppm RMS
  - Initialization Time: < 10 s
  - Initialization Reliability: > 99.9%
- Post-processing Static:
  - Horizontal: 8 mm + 1 ppm RMS
  - Vertical: 10 mm + 2 ppm RMS

## Communications

- Integrated 3G network modem
- UHF Modem Internal Rx: 450 MHz to 470 MHz
- UHF Modem External Tx DL6: 1 W to 28 W adjustable
- Protocols:
  - RTCM2.x, RTCM3.x, CMR
  - NMEA 0183 output
  - HCN outputs for GNSS raw data (convertible to RINEX static format)
- Bluetooth®: V2.0
- Serial: 1 x 10-pin LEMO port (external power, USB data download, USB update, RS-232)
- Data Storage:
  - 4 GB internal memory
  - GPS device mounts as a USB external hard drive

## Physical

- Size (H x D): 80 mm x 180 mm (3.1 in x 7.1 in)
- Weight: 1.4 kg (49.4 oz) with battery
- Environment
  - Operating: -40°C to +65°C (-40°F to +149°F)
  - Storage: -40°C to +75°C (-40°F to +167°F)
- Humidity: 100% condensation
- Dust and Water Proof: IP67
- Shock and Vibration: 2 m (6.56 ft) fall onto concrete

## Electrical

- Power Consumption: 3.5 W (depending on user settings)
- Li-ion Battery Capacity: 3400 mAh
- Operating Time<sup>(2)</sup>: Up to 4 h in RTK mode
- External Power: 9 V DC to 18 V DC

## Software (optional)

- LandStar 7 Android field data collection software

(1) Accuracy and reliability specifications may be affected by multi path, satellite geometry and atmospheric conditions. Performances assume minimum of 5 satellites, follow up of recommended general GPS practices. (2) Operating time varies based on temperature.

Specifications are subject to change without notice.



© 2017 Shanghai Huace Navigation Technology Ltd. All rights reserved. The Bluetooth® world mark and logos are owned by Bluetooth SIG, Inc. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners – Rev. Nov 2017

CHC - Shanghai Huace Navigation Technology Ltd.  
599 Gaojing Road, Building C  
201702, Shanghai, China  
Tel : +86 21 542 60 273