

M5+

Survey & Engineering

- 384 channels multi-constellation receiver
- Multiple frequencies for GPS, GLONASS and BDS
- Integrated network, UHF modem and Bluetooth
- Compact and rugged design
- Cost-effective GNSS RTK



M5+ GNSS receiver is one of the most cost-effective solutions selected by a large number of surveyors for its outstanding performances and reliability.

Outstanding 384 channels multi-constellation tracking supports GPS, GLONASS and BDS for obstructed sky conditions to guarantee RTK accuracy and reliability in the field.

Perfect compatibility with Android-based field surveying software LandStar 7 provides an epoch-making experience for various and flexible working industries.

M5+ innovative design integrates a built-in GNSS core, multi-constellation antenna, Bluetooth communication, Rx/Tx UHF datalink and network modules in one single receiver.

M5+ GNSS receiver brings extremely affordable GNSS RTK solution to surveyors without a high cost.



■ Technical Specifications

GNSS Characteristics

- 384 channels with all in view simultaneously tracked satellite signals
 - GPS: L1, L2, L5
 - GLONASS: L1, L2
 - BDS: B1, B2, B3
- Advanced multipath mitigation technology
- Low noise carrier phase measurement

GNSS Accuracies ⁽¹⁾

- Real Time Kinematics (RTK):
 - Horizontal: 10 mm + 1 ppm RMS
 - Vertical: 15 mm + 1 ppm RMS
 - Initialization Time: < 10 s
 - Initialization Reliability: > 99.9%
- Post-processing Static:
 - Horizontal: 8 mm + 1 ppm RMS
 - Vertical: 10 mm + 2 ppm RMS

Communications

- Integrated 3G network modem
- UHF Radio: Protected TNC Female
 - Standard Internal Rx/Tx: 450 MHz to 470 MHz
 - Transmit Power: Up to 2 W
 - Protocol: CHC
 - Range: 5 km under optimal conditions
 - External Tx DL6: 5 W to 28 W adjustable
- Protocols:
 - RTCM2.x, RTCM3.x, CMR
 - NMEA 0183 output
 - HCN outputs for GNSS raw data (convertible to RINEX static format)
- Bluetooth®: V2.0
- Serial: 1 x 10-pin LEMO port (external power, USB data download, USB update, RS-232)
- Data Storage:
 - 4 GB internal memory
 - GPS device mounts as a USB external hard drive

Physical

- Size (H x D): 80 mm x 180 mm (3.1 in x 7.1 in)
- Weight: 1.4 kg (49.4 oz) with battery
- Environment
 - Operating: -40°C to +65°C (-40°F to +149°F)
 - Storage: -40°C to +75°C (-40°F to +167°F)
- Humidity: 100% condensation
- Dust and Water Proof: IP67
- Shock and Vibration: 2 m (6.56 ft) fall onto concrete

Electrical

- Power Consumption: 3.5 W (depending on user settings)
- Li-ion Battery Capacity: 3400 mAh
- Operating Time⁽²⁾: Up to 4 h in RTK mode
- External Power: 9 V DC to 18 V DC

Software (optional)

- LandStar 7 Android field data collection software

(1) Accuracy and reliability specifications may be affected by multipath, satellite geometry and atmospheric conditions. Performances assume the minimum of 5 satellites, follow up of recommended general GPS practices. (2) Operating time varies based on temperature.

Specifications are subject to change without notice.



© 2018 Shanghai Huace Navigation Technology Ltd. All rights reserved. The Bluetooth® world mark and logos are owned by Bluetooth SIG, Inc. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners – Rev. Apr 2018

CHC - Shanghai Huace Navigation Technology Ltd.
599 Gaojing Road, Building D
Shanghai, 201702, China
Tel : +86 21 542 60 273