

CHCNAV

CGI-610

GNSS/INS SENSOR



NAVIGATION &
INFRASTRUCTURE

TIGHTLY COUPLED HIGH-PERFORMANCE GNSS/INS SYSTEM

The CGI-610 GNSS/INS sensor is a high-precision dual-antenna receiver providing reliable and accurate navigation and positioning solutions for demanding ground, marine or aerial applications. Specifically designed to meet the requirements of 3D control and autonomous vehicle guidance applications, the CGI-610 is particularly efficient in urban canyons, when GNSS signals are lost and in other harsh environments where navigation results are easily degraded.

The tight fusion of the latest GNSS technology with an industrial-grade MEMS IMU is powered by CHCNAV algorithms to provide accurate hybrid position, attitude and velocity data up to 100 Hz. With its extremely rugged and lightweight enclosure, the CGI-610 GNSS/INS sensor is built to meet the highest protection standards and ensure uninterrupted performance.

ROBUST POSITIONING AND ATTITUDE

GNSS + MEMS IMU

Tightly integrated dual-antenna GNSS technology with industrial MEMS IMU provides continuous, reliable and high-precision real-time positioning and orientation data, even in complex and obstructed environments where GNSS outages occur.

EXTENDED CONNECTIVITY AND WEB CONFIGURATION

Rich hardware interfaces make the integration seamless in all applications

The CGI-610 GNSS/INS offers high connectivity integration to achieve accurate positioning and attitude from GNSS NTRIP/TCP corrections. RTK centimeter initialization is fast and reliable to ensure that you can get started in a fraction of time. With its Ethernet port, serial ports, CAN and low latency PPS output, the CGI-610 GNSS/INS sensor offers unsurpassed compatibility for a wide range of industrial and machine applications.

EXTERNAL SENSOR INPUT

Odometer sensor support for ultimate results

When longer GNSS outages are likely to be encountered (tunnels, bridges,...), an external odometer sensor for terrestrial vehicles can provide an additional independent measurement of displacement and velocity, which is fused with the GNSS/INS navigation solution.

HIGH-FREQUENCY OUTPUTS

Up to 100 Hz data

The CGI-610 is a powerful GNSS/INS system supporting data output up to 100 Hz to meet the requirements of highly dynamic applications (airplane, train, car, ...). Its versatile design allows a perfect integration in many applications where uninterrupted performance is required, such as marine, industrial automation, robotics, machine control, port automation...

HIGH-RELIABILITY INDUSTRIAL DESIGN

Secure your investment in any machine control application

IP67 dust and water resistant certification and industrial-grade power management integrated circuit guarantee reliable and consistent operation in the harshest environments. The CGI-610 is vibration and shock resistant and is protected against electrostatic discharge.



**RUGGED
GNSS/INS FUSION**



RELIABLE POSITION AND ATTITUDE

SPECIFICATIONS

Performance

Channel	1408 Channels
---------	---------------

Signal Tracking

Position Antenna

GPS	L1C/A, L2C, L2P(Y), L5
BDS	B1I, B2I, B3I
GLONASS	G1, G2
GALILEO	E1/E5a/E5b
SBAS	L1C/A
QZSS	L1C/A, L2C, L5

Vector Antenna

GPS	L1C/A, L2C, L2P(Y), L5
BDS	B1I, B2I, B3I
GLONASS	G1, G2
GALILEO	E1/E5a/E5b
QZSS	L1C/A, L2C, L5
Attitude Accuracy(RMS)	0.1°(Baseline Length ≥ 2 m)
Positioning Accuracy (RMS)	Single 1.2 m DGPS 0.4 m RTK 1 cm+1 ppm

Maximum Data Update Rate

RTK Position	20 Hz
INS Position/Attitude	100 Hz
Speed Accuracy(RMS)	0.03m/s
PPS Time Synchronization Accuracy(RMS)	20ns
Initialization Time(RMS)	< 60 seconds
Initialization Reliability	> 99.9%
Signal Reacquisition(RMS)	≤ 2 seconds
Time to First Fix(RMS)	Cold start ≤ 45 seconds

IMU Performance

Gyroscope Performance

Gyro Type	MEMS
Gyro Range	±300 deg/s
Gyro Bias Instability (Allan, 1σ)	2.7 deg/s
Angular Random Walk (Allan, 1σ)	0.1°/√h

Accelerometer Performance

Accelerometer	±6 g
Accelerometer Bias Instability(Allan, 1σ)	15 μg
Velocity Random Walk(Allan, 1σ)	0.035 m/sec/√hr

Communication Ports

1 x RJ45	
3 x RS232 Serial Port	Up to 460,800 bps
1 x CAN	Up to 1 Mbps
1x Mini USB	
Wi-Fi	802.11 b/g/n
Network Modem	LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B18 B19/B20/B25/B26/B28 LTE-TDD: B38/B39/B40/B41 UMTS: B1/B2/B4/B5/B6/B8/B19 GSM: B2/B3/B5/B8
1 x 4G Antenna Port	TNC
2 x GNSS Antenna Connector	TNC
1 x PPS	SMA
1 x Power Interface	DC5525

Environmental

Operating Temperature	-40°C to +75°C
Storage Temperature	-40°C to +85°C
Humidity	95% Non-condensing
Water/Dust Rating	IP67
Vibration	MIL-STD-810G
Shock	IEC-60068-2-27
Anti-static	ISO10605 Contact ±8 kv Air ±15 kv

Included Accessories

1 x Power cable
1 x 19 PIN cable
2 x GNSS Antenna
1 x 4G Antenna
2 x Magnetic antenna holder

Physical And Electrical

Size	169 mm × 121 mm × 55 mm
Weight	1.15 kg
Input voltage	9 ~ 32 VDC (Standard Adaptation 12 VDC)
Power	< 5 W (Typical)

*All specifications are subject to change without notice.
© 2023 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHCNAV and CHCNAV logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision April 2023.

Performance During GNSS Outages

Outage Duration	Positioning Mode	Position Accuracy (m) RMS		Velocity Accuracy (m/s) RMS		Attitude Accuracy (degree) RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0 s	RTK	0.02	0.03	0.02	0.02	0.08	0.08	0.08
10 s	RTK	0.20	0.10	0.05	0.02	0.10	0.10	0.12

WWW.CHCNAV.COM | MARKETING@CHCNAV.COM

CHC Navigation Headquarter
Shanghai Huace Navigation Technology Ltd.
577 Songying Road, Qingpu,
201703 Shanghai, China
+86 21 54260273

CHC Navigation Europe
Infopark Building, Sétány 1,
1117 Budapest, Hungary
+36 20 421 6430
Europe_office@chcnav.com

CHC Navigation USA LLC
6380 S. Valley View Blvd, Suite 246,
Las Vegas, NV 89118, USA
+1 702 405 6578

CHC Navigation India
409 Trade Center, Khokhra Circle,
Maninagar East, Ahmedabad,
Gujarat, India
+91 90 99 98 08 02